EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER

2000094454

PUBLICATION DATE

04-04-00

APPLICATION DATE

25-09-98

APPLICATION NUMBER

10287371

APPLICANT: NIKON CORP;

INVENTOR: YAMAZAKI MASAAKI;


INT.CL.

B29C 33/42 G02B 3/00 // B29L 11:00

TITLE

MOLDING DIE AND MANUFACTURE

OF OPTICAL ELEMENT



ABSTRACT :

PROBLEM TO BE SOLVED: To provide a molding die which does not form wrinkles even when a mumber of dents are formed.

SOLUTION: Since this molding die comprises a die base metal 4 having a mumber of pores and an electroless nickel plating layer 5 coating the surface to be molded, when a dent for element 3b is to be formed, the electroless nickel plating layer 5 is deformed in accordance with the surface shape of an indenter on a cavity surface 3a, and the die base metal 4 is also recessed while reducing the volume of the pores in accordance with the surface shape of the indenter. In other words, since the volume change due to the deformation in a process of dents is absorbed in the pores of the die base metal 4, wrinkles are hardly formed around the dents for element 3b, so that the wrinkles can be prevented from being formed on the surface of an array of microoptical element to be molded by the resultant molding die.

COPYRIGHT: (C)2000,JPO